



Earth Moving 24hp Mini Stand-On Skid Steer



35in Width



24 Horsepower



2,227lbs Tipping Capacity

The Makinex 24hp Mini Stand-On Skid Steer delivers powerful performance in a compact design, making it ideal for tight job sites where maneuverability is key. With a width of just 35in, this versatile machine easily fits through narrow spaces while offering an impressive tipping capacity of 2,227lbs. Powered by a Yanmar 3TNV80F diesel engine, it delivers 24hp with smooth hydraulic operation, ensuring efficiency and reliability for heavy-duty lifting, grading, and material handling. The Makinex Skid Steer features premium, globally sourced parts, including Sumitomo Riko hydraulic lines (Japan), Hansa TMP pumps (Italy), Walvis control valves, Danfoss motors, and Donaldson filtration.



IDEAL FOR:



**Tight-Space
Excavation**



**Material
Handling**



**Landscaping
& Site Prep**



**Demolition & Debris
Removal**



**Utility & Trenching
Work**



**Agriculture &
Farming**

SPECIFICATIONS:

DIMENSIONS (STD)		PERFORMANCE	
Height to Bucket Hinge Pin, max	76 in	Ground drive speed, forward and reverse	3.9 mph
Operating Height, max std.bucket	106.9 in	Ground pressure, 8 in (200 mm) tracks	0.35 bar
Machine Height	51.7 in	Angle of Departure	22°
Length without Attachment	71.9 in	Tipping capacity	2,227 lbs
Length with Standard Bucket	98.2 in	Operating capacity (35% of tipping capacity)	780 lbs
Ground Clearance	5.7 in	Machine weight (no attachment, fluids full)	2,712 lbs
Ground Contact Length	37.8 in	Auxiliary Hydraulic Flow	13.5 gal/min
Width	35 in	Auxiliary Hydraulic Pressure	180 Bar
POWER		Battery 12 V; 60 Ah	475 cold cranking amps @ 0°F
Engine Yanmar 3TNV80F diesel	EU Stage V/ EPA Tier 5 Final		
Number of cylinders	3	FLUID CAPACITIES	
Displacement	1.267 L	Fuel tank	9.0 gal
Bore	3.15 in		
Stroke	3.31 in	Engine oil, with filter	1.3 gal
Gross power rating (per SAE J1955)	17.8 kW	Hydraulic System	11 gal
Rated engine speed	3000 rpm		




FEATURES:



1. Stand-On Operator Platform



2. Compact 35in Width



3. Yanmar 3TNV80F Diesel Engine




4. 2,227lbs Tipping Capacity



5. 13.5 gal/min Hydraulic Flow




6. 3.9 mph Travel Speed



7. Two sets of Quick Couplers



8. Wide selection of Attachments



9. Heavy Duty Frame



10. Easy access to all Engine Components

MAKINEX MINI DUMPER RANGE



1. HG Gas 1t Mini Dumper (Hi Tip)